



## Groundwater Modeling for Closure of the Little Blue Run CCR Disposal Area

Prepared For  
**2017 NGWA GROUNDWATER SUMMIT**  
**NASHVILLE, TN**  
**DECEMBER 4-7, 2017**

Presented By  
**Brianne J. Hastings and**  
**H. Thomas Walsh**  
 Civil & Environmental Consultants, Inc.  
 333 Baldwin Rd. Pittsburgh, PA 15205

FirstEnergy Generation, LLC




### Introduction Little Blue Run CCR Disposal Impoundment

- ▶ Located in Beaver County, PA and Hancock County, WV
- ▶ Disposal area for FirstEnergy's Bruce Mansfield Station
- ▶ In use since 1975 for CCR disposal



FirstEnergy

CEC  
 Civil & Environmental Consultants, Inc.



FirstEnergy

CEC  
 Civil & Environmental Consultants, Inc.


### Introduction Little Blue Run CCR Disposal Impoundment



- ▶ Impoundment formed behind 400 ft. high dam
- ▶ LBR Valley is dominated by steep slopes and drains to the Ohio River
- ▶ CCR was pumped as a slurry from the power station to the impoundment
- ▶ Low permeability CCR solids settle filling Little Blue Run Stream valley
- ▶ Standing water present over portions of CCRs

FirstEnergy

CEC  
 Civil & Environmental Consultants, Inc.



FirstEnergy

Currently 952 Acres

CEC  
 Civil & Environmental Consultants, Inc.

### Closure Plan


- ▶ Consent decree entered in 2012, requiring cessation of CCR disposal at LBR on December 31, 2016
- ▶ Major permit modification approved to
  - Reduce standing water and main pool
  - Place geomembrane liner, cushion geotextile, and one foot thick final cover soil layer
- ▶ Closure to be performed over 15 years,
  - The final permit was approved to occur over 12 years, completing in 2028



FirstEnergy

CEC  
 Civil & Environmental Consultants, Inc.

**Proposed Phasing Plan for Closure**



FirstEnergy

CEC  
Civil & Environmental Consultants, Inc.

**Model Purpose**

- ▶ Elimination of standing water and capping expected to greatly reduce water levels within CCR material
- ▶ Water level changes expected to significantly impact settlement, slopes, and surface drainage.
- ▶ Groundwater modeling was performed to prepare a prediction of water level drawdown
- ▶ Water level drawdown was used to perform a settlement analysis




FirstEnergy

CEC  
Civil & Environmental Consultants, Inc.

**Groundwater Modeling**

- ▶ Computer software used to simulate groundwater flow field during and after closure
- ▶ Based on an interpretation of geological, hydrological, and site-specific conditions.



FirstEnergy

CEC  
Civil & Environmental Consultants, Inc.



**Groundwater Model Build-Out**

- ▶ Model area separated horizontally into model cells.
  - 130 Rows
  - 120 Columns
  - Variable size to show greater detail over impoundment
  - Cell size range 112' by 112' to 900' by 900'
- ▶ Model area separated vertically into layers.
  - 9 Layers
    - 5 Aquifers
    - 4 Aquitards


	A	B	C	D	E	F	G
1							
2							
3							
4							
5							
6							
7							
8							
9							




http://www.blog.whon.com  
CEC  
Civil & Environmental Consultants, Inc.

FirstEnergy

LBR Model Grid  
130 Rows  
120 Columns  
Variable size




LBR Model Grid  
130 Rows  
120 Columns  
Variable size




Layer 4A Aquitard

LBR Model Grid  
130 Rows  
120 Columns  
Variable size




Layer 4 Worthington Aquifer

LBR Model Grid  
130 Rows  
120 Columns  
Variable size




Layer 3A Aquitard

LBR Model Grid  
130 Rows  
120 Columns  
Variable size




Layer 3 Freeport Aquifer

LBR Model Grid  
130 Rows  
120 Columns  
Variable size




Layer 2A Aquitard

LBR Model Grid  
130 Rows  
120 Columns  
Variable size




Layer 2 Lower Glenshaw Aquifer

LBR Model Grid  
130 Rows  
120 Columns  
Variable size



LBR Model Grid  
130 Rows  
120 Columns  
Variable size






### Model Calibration







- ▶ Model calibrated to match observed water levels in the various aquifers and observed hydrologic volumetric budget
- ▶ Input Parameters Modified:
  - Boundary Conditions
  - Recharge – based on HELP modeling
  - Horizontal and Vertical Hydraulic Conductivities
    - Aquifers
    - Aquitards
    - Weathering rind
    - Fracture traces
    - CCR












FirstEnergy

EEC  
Civil & Environmental Consultants, Inc.









## Conclusions

- ▶ (1) Reductions in water levels within the CCR will be realized prior to cap placement because of reductions in the aerial extent of standing water pools within LBR.
- ▶ (2) Reductions in water levels will occur within the CCR at a higher rate after cessation of pumping CCR, reduction of the main pool, and initiation of cap placement.
- ▶ (3) The majority of draw-down within the CCR may occur in less than 30 years of the cessation of pumping CCR and the initiation of cap placement, with a smaller percentage of additional draw-down happening after.

FirstEnergy

CEC  
Civil & Environmental Consultants, Inc.

## Conclusions

- ▶ (4) The greatest amount of draw-down within the CCR will be realized in the northern and central portions of the impoundment where the CCR deposits are thickest.
- ▶ (5) Only portions of CCR in Layer 1 completely dewater over the course of the 250 year model simulation.

FirstEnergy

CEC  
Civil & Environmental Consultants, Inc.

FirstEnergy

CEC  
Civil & Environmental Consultants, Inc.

